

## Specification Guide for Popular Sanitary Pump Models

<b>Flow Range ml/min (gal./hr.)</b>	<b>Max Pressure psig (bar)</b>	<b>Wetted Parts</b>	<b>Pump Model</b>	<b>Electrical</b>
0-1.92 (.03)	75 (5.17)	Ceramic 316SS Teflon	QG6- Q1SAN	115 VAC, 60 Hz.
0-6.4 (.10)	50 (3.5)	Ceramic 316SS Teflon	QG20- Q1SAN	115 VAC, 60 Hz.
0-16 (.25)	100 (6.9)	Ceramic 316SS Teflon	QG50- Q1SAN	115 VAC, 60 Hz.
0-48 (.76)	100 (6.9)	Ceramic 316SS Teflon	QG150- Q1SAN	115 VAC, 60 Hz.
0-128 (2.02)	100 (6.9)	Ceramic 316SS Teflon	QG400- Q1SAN	115 VAC, 60 Hz.
0-552 (8.6)	100 (6.9)	Ceramic 316SS Teflon	QD- Q1SAN	115 VAC, 60 Hz.
0-1242 (18.9)	50 (3.5)	Ceramic 316SS Teflon	QD- Q2SAN	115 VAC, 60 Hz.